

What's new

For a full description of what is contained in each release, see AXIS Camera Station Pro release notes.

If you've upgraded from AXIS Camera Station 5 to AXIS Camera Station Pro, take a look at the AXIS Camera Station Installation and migration guide to make sure your solution functions as expected.

## **AXIS Camera Station Pro 6.4**

## **AXIS Camera Station Pro 6.4**



From the new diagnostics page, you can:

- Generate a system report
- View client and server configuration sheets
- Access the Axis Online services status page
- Restart the service remotely

See *Diagnostics* and *Restart the service* in the AXIS Camera Station Pro user manual for more information.

#### Remote service restart

• You can now restart your AXIS Camera Station Pro service remotely, making, for example, maintenance and troubleshooting more convenient. See *Restart the service in the AXIS Camera Station Pro user manual* for more information.

#### Select any audio channel

• You can now select any audio input from devices with two inputs, such as the AXIS FA54 and the AXIS D3110 Connectivity hub, and associate them with a video source.

#### 3x3 split view on AXIS D1110

• The AXIS D1110 Video Decoder can now display up to 9 video streams. See *Multiple monitors in the AXIS Camera Station Pro user manual* for more information.

### **AXIS Camera Station Pro 6.3**

## **AXIS Camera Station Pro 6.3**



#### Action rules

- The new Live view trigger occurs when a user opens a specific camera's video stream. You can use this, for example, to let people near a camera know that someone's watching them using the camera's LEDs. See *Create live view triggers in the AXIS Camera Station Pro user manual* for more information.
- The new Virtual I/O action triggers a specific virtual input port on a device. See Create virtual I/O actions in the AXIS Camera Station Pro user manual for more information.
- When you add a camera with an indication LED, like AXIS Q9307, AXIS Camera Station Pro creates an action rule with the new Live view trigger and Virtual I/O action.

#### More searchable vehicle properties


• New vehicle properties in data search, like color, direction, and country, make it easier to find the event you're looking for. See *Data search in the AXIS Camera Station Pro User manual* for more information.

#### Secure entry

- You can now turn on or off access rules in the access management system using action rules. See *Create access control actions in the AXIS Camera Station Pro user manual* for more information.
- With the added support for AXIS A4612 Bluetooth Reader and the new mobile credential in AXIS Camera Station Mobile App, cardholders can now unlock doors using their phone. See Use a mobile phone to unlock a door in the AXIS Camera Station Pro user manual for more information.
- The new door type monitoring door is different from a regular door with a door monitor. A regular door with a door monitor supports locks and readers but requires a door controller. A monitoring door supports one door position sensor but only requires a network I/O relay module connected to a door controller. See Add a monitoring door in the AXIS Camera Station Pro user manual for more information.

## **AXIS Camera Station Pro 6.2**

## **AXIS Camera Station Pro 6.2**



#### Replace a camera with multiple views

- You can now replace a camera with more than one view as long as the replacement camera has the same number of views as the old camera.
- See Replace a device in the AXIS Camera Station Pro User manual for more information.

#### User permission for data search

- As an administrator, you can now remove access to data search for operators. This feature can help align with personal data regulations.
- See Configure user permissions in the AXIS Camera Station Pro User manual for more information.

#### Filter on server in data search

- You can now filter servers in data search live mode in a multi-server system.
- See Data search in the AXIS Camera Station Pro User manual for more information.

#### Compatible with the new network I/O relay module from Axis

- AXIS Camera Station Pro is compatible with the new AXIS A9210 Network I/O Relay Module. Using a single IP address, you can expand the unit to 128 I/Os. Using the device event option in action rules, you can easily integrate the inputs and outputs into AXIS Camera Station Pro.
- Go to AXIS A9210 product page on axis.com for more information.

### **AXIS Camera Station Pro 6.1**

## **AXIS Camera Station Pro 6.1**



In addition to the capabilities available in AXIS Camera Station, AXIS Camera Station Pro also offers the following:

#### Cloud services through Axis Cloud Connect

- Automatic license management
- Server monitoring
- Web client
- Device management
- User management
- See Manage connected services in the AXIS Camera Station Pro user manual for more information.

#### Web client for AXIS Camera Station Pro

- Provides access to AXIS Camera Station Edge and AXIS Camera Station Pro recordings and live video in your web browser.
- Choose to access the system on a private network using the AXIS Camera Station Pro web client or access your system from anywhere with the AXIS Camera Station Cloud web client.
- Includes predefined views, PTZ, and preset positions.
- See Web client for AXIS Camera Station user manual for more information.

#### Axis data insights dashboard

- Visualizes analytics data from your devices
- Analytics data includes crossline counting and occupancy in area scenarios configured in AXIS Object Analytics on the devices in your system.
- See Axis data insights dashboard in the AXIS Camera Station Pro user manual for more information.

#### Replace a camera

- You can now replace an Axis camera while keeping compatible settings and existing recordings.
- This feature works best with cameras of the same model or similar ones.
- See Replace a device in the AXIS Camera Station Pro user manual for more information.

#### Kerberos authentication

### **AXIS Camera Station Pro 6.1**

- AXIS Camera Station Pro uses the Microsoft Negotiate protocol (SPNEGO) which means that Kerberos is the preferred and default authentication protocol.
- See Authenticate using Kerberos in the AXIS Camera Station Pro System hardening guide for more information.

#### View components

- The component page lets you manage components and view their status.
- See Components in the AXIS Camera Station Pro user manual for more information.

#### Optimize for storage

- Optimize for storage uses more advanced compression tools to save additional storage compared to the default Zipstream setting.
- This profile can further reduce the bitrate even for scenes with a lot of motion.
- See Edit stream profiles in the AXIS Camera Station Pro user manual for more information.

#### Double swipe

- The double-swipe allows a cardholder override the current state of a door.
- For example, they can use it to unlock a door outside the regular schedule, which is more convenient than going into the system to unlock the door.
- See Door security level in the AXIS Camera Station Pro user manual for more information.

#### Two-person rule

- The two-person rule requires two people to swipe their cards to gain access.
- See Door security level in the AXIS Camera Station Pro user manual for more information.

What's new AXIS Camera Station Pro © Axis Communications AB, 2023 - 2024 Ver. M4.3 Date: November 2024 Part no. T10196861